UF1-30 and UF1-65



Small single bag filter housing UF1-30 and UF1-65

Bag filters are being uses in the filtration of liquids containing higher concentrations of coarse solids, handling batches of (various) liquids and as endfiltration or polishing of liquids with minor concentrations of solids.

amafilter – LFC Lochem (Filtration Group Process Systems) has a small bag filter housing available, UF1, for size 30 and size 65 filter bags. UF1 is suitable to handle small liquid batch processes.

Features

- Easy to use, easy to clean, and accessibility
- Cover opens without disconnecting piping
- Strong stainless metal heavy duty support basket
- Suitable to use as a strainer instead as bag filter
- Cover closure with V-band quick release clamp
- Swing bolts for 300 psi design pressure

Filter bags

Filtration Group supplies a wide range of filter bags in different materials, pore sizes, dimensions and models to fit in our housings as well as those of other manufacturers. For detailed information about amaFlow filter bags, please visit our website www.ama-lfc.com.



A www.ama-lfc.com



Typical aplication

Filtration of general industrial liquids

Standard specification

- PED 2014/68/EU: article 4 paragraph 3
- Design pressure: 7, 14 or 21 bar
- Design temperature: 0 / 90 °C
- Operating temperature: depending on the filter media and gaskets used
- Side-inlet and bottom-outlet
- Manufacture from carbon steel or stainless steel
- Perforated stainless steel support basket
- O-ring sealing: standard Buna N. Other materials on request.
- For size 30 or size 65 filter bags with a collar-ring
- Not recommended to use in food and beverage application

Customized requirements

We understand that our customer's facing complex processes and environmental requirements. There where a standard filter housing could not be sufficient, our engineers are able to design a custom made filtration solution.

For further information please contact us at www.ama-lfc.com





Filtration Group BV – amafilter – LFC Lochem Hanzeweg 21, 7241 CS Lochem Postbus 35, 7240 AA Lochem The Netherlands [KvK] 37048847 [t] +31 57 329 77 77 [e] info@filtration.group [i] www.ama-lfc.com

Connections

- N1 Inlet
- N2 Outlet
- N3 Vent

Dimensions*

Size	А	В	С
	[mm]	[mm]	[mm]
30	349	414	114
65	698	828	114

Ordering information

Example:	1 2 3 4 5 UF1-65-1.5-B4N-100		
1 Туре	= UF1		
2 Dimension			
30	= size 30		
65	= size 65		
3 Connection			
1	= 1" NPT (for size 30)		
1.5	= 1,5" NPT (for size 65)		
4 Material			
A4N	= carbon steel		
B4N	= stainless steel 304		
C4N	= stainless steel 316		
5 Pressure design			
100	= 100 psi (7 bar)		
200	= 200 psi (14 bar)		
300	= 300 psi (21 bar)		

* Dimensions are for reference only. Use dimensional drawing for installation purposes. Subject to technical alteration without prior notice.

© 2018 Filtration Group BV. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this document concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Filtration Group BV as to the effects of such use or the results to be obtained. Filtration Group BV assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.



